ADARA AL11400 DOWNLIGHT

IP65 IK06

Benefits

- Powerful LEDs offer energy savings and cost reduction for maintenance
- Luminaire housing has a high resistance to UV and is treated with highly antioxidant water-repellent lubricating solution to lengthen lifespan
- Available in anthracite or light grey for architectural use
- Highly efficient thermoplastic with high vacuum deposit for heightened luminaire care
- 15° or 50° beam option offers effective downlighting
- Ability to be used as either a down or uplighter
- Design allows for ease of maintenance

Technical Features

- Surface mounted floodlight
- Integral driver
- Double powder coated polyester finish with high resistance to UV and oxidation
- Sealed to IP65
- Stainless steel A4-70 treated external fixings
- Extruded aluminium housing EN AW-6063 T5 / EN-AB 47100
- Soda-lime tempered glass 4mm
- Silicon sealing gasket
- Polypropylene cable gland M16 Ø5, 5 / 10mm

Applications

- Architectural
- Surface Mounted

Beam Types

- 15°
- 50°

Colours

- Anthracite
- Light grey

	Lamp Wattage	Power Supply	LED	Beam	Colour Temp.**	LED Driver	Lm	Fixture Colour
AL11401	26W	220-240V 50/60HZ	1 LED	15°	3000	Integral	2760	Anthracite
AL11402	26W	220-240V 50/60HZ	1 LED	15°	3000	Integral	2760	Light Grey
AL11403	26W	220-240V 50/60HZ	1 LED	50°	3000	Integral	2760	Anthracite
AL11404	26W	220-240V 50/60HZ	1 LED	50°	3000	Integral	2760	Light Grey

** Other colour temperatures available on request

Key features

1.



Dimensions

2.



Polar Intensity Diagram



Beams

AL11401 & AL11402
Luminaire: 26W 3000K
Lamp: 1 LED
Power: 220-240V 50/60HZ

3.



Polar Intensity Diagram



Beams

AL11403 & AL11404
Luminaire: 26W 3000K
Lamp: 1 LED
Power: 220-240V 50/60HZ

All dimensions are in mm.