REGIA AL11300









- Powerful LEDs offer energy savings and cost reduction for maintenance
- Luminaire housing has a high resistance to UV and is treated with highly antioxidant water-repellent lubricating solution to lengthen lifespan
- · Quick and easy adjustment is possible with the mechanical system and graduated ring nut allows for accurate positioning, fitting can also be locked in place to ensure correct beam direction
- 99.99% Pure aluminium high vacuum deposit for heightened luminaire care
- Design allows for ease of maintenance

Technical Features

- Surface mounted floodlight
- Integral driver

- Double powder coated polyester finish with high resistance to UV and oxidation
- Positionable with a mechanical system which can be locked or adjusted on the vertical axis, a graduated ring nut allows for accurate positioning
- Sealed to IP65 and IK09 rated
- Stainless steel A4-70 treated external fixings
- · Available in anthracite or light grey for architectural use
- Extruded aluminium housing EN AW-6063 T5 / EN-AB 47100
- Soda-lime tempered glass 6mm
- Silicon sealing gasket
- Cable gland M20 13.5 Ø 7 / 13mm



Applications

- Architectural
- Surface Mounted

Beam Types

- 8°
- 24°
- 62°

Colours




Anthracite




	Lamp Wattage	Power Supply	LED	Beam	Colour Temp.**	LED Driver	Lm	Fixture Colour
AL11301	47W	220-240V 50/60HZ	1 LED	8°	3000	Integral	5197	Anthracite
AL11302	47W	220-240V 50/60HZ	1 LED	8°	3000	Integral	5197	Light Grey
AL11303	47W	220-240V 50/60HZ	1 LED	24°	3000	Integral	5197	Anthracite
AL11304	47W	220-240V 50/60HZ	1 LED	24°	3000	Integral	5197	Light Grey
AL11305	47W	220-240V 50/60HZ	1 LED	62°	3000	Integral	5197	Anthracite
AL11306	47W	220-240V 50/60HZ	1 LED	62°	3000	Integral	5197	Light Grey

^{**} Other colour temperatures available on request

Key features



Dimensions




AL11301 & AL11302

Luminaire: 47W 3000K

Lamp: 1 LED


Power: 220-240V 50/60HZ



AL11303 & AL11304 Luminaire: 47W 3000K

Lamp: 1 LED

Power: 220-240V 50/60HZ



AL11305 & AL11306

Luminaire: 47W 3000K

Lamp: 1 LED

Power: 220-240V 50/60HZ