

VOLANS AL11801



Benefits

- Adjustable bracket increases installation capability and can be adjusted for false ceilings
- Luminaire housing has a high resistance to UV and is treated with highly antioxidant water-repellent lubricating solution to lengthen lifespan
- Body treatment ensures easy opening of the product for maintenance purposes
- Available in a spotlight, medium or flood reflector options for use across a large architectural application

- Die-cast aluminium body to EN AB 44100 with high resistance to oxidation
- 2 mm thick AISI 316L stainless steel trim
- Aluminium ring with adjustable bracket for mounting
- Protective undercoating phosphochromate treatment
- Sealed to IP67
- IK07 rated
- Classification: class I
- Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
- Soda-lime tempered glass 5mm
- Silicon sealing gasket
- Cable gland M16 Ø 5/10mm
- Driver sold separately
- IP boxes for driver available upon request

Applications

- Architectural
- Ceiling recessed

Colours

- Stainless

Technical Features

- Ceiling recessed downlighter
- Integral LED
- Clear diffuser
- Double powder coating polyester with high resistance to UV and oxidation

	Lamp Wattage	Power Supply	LED	Beam	Colour Temp.	Lm	Driver	Fixture Colour
AL11801	18W	Max 500 mA DC	1 LED	62°	4000	2045	Sold separately*	Stainless
AL11802	18W	Max 500 mA DC	1 LED	62°	3000	1957	Sold separately*	Stainless

Key features

1.

Dimensions

All dimensions are in mm.

2.

Polar Intensity Diagram

Beams

AL11801
Luminaire: 18W 4000K

AL11802
Luminaire: 18W 3000K

* Driver and IP boxes sold separately, please enquire when quoting or ordering.